



NEW TRIGGER POSITIONING
LANYARD RANGE

Now part of



capital

S A F E T Y

a 3M company

COMPLETE SAFETY RANGE OF NEW IMPROVED WORK POSITIONING LANYARD WITH TRIGGERS

GLOBAL LEADER
IN FALL PROTECTION



NEW TRIGGER POSITIONING LANYARD RANGE

The new improved adjustment systems developed for the new Black Triggers gives the option to easily adjust the length of the lanyard during use, even in harsh environments when the rope is wet and dirty.



NEW DBI-SALA® POSITIONING LANYARD RANGE

The new DBI-SALA® adjustment system has been improved to give the option to easily adjust the length of the lanyard during use. These new versions have a double action carabiner KJ5024 with an aluminium snaphook (ref: AJ567) and are available in different lengths.

DESCRIPTION: Braided rope, diameter 11 mm.
All models, except 1200312, have a blue protective cover on the rope. 1200312 has a protective cover on the trigger.

LENGTH OF THE ROPE COVER:
2 m to 5 m rope = 0.5 m rope cover
10 m rope = 2 m rope cover

MAX WEIGHT CAPACITY: 140 kg.



CE EN358 CE EN362

| New Ref | Old Ref | Adjustment | Rope Diameter | Double Action Carabiner | | | Connector | Single Action Carabiner | | | Weight (kg) | |
|------------------------------|-----------|--------------|---------------|-------------------------|-------|---|-----------|-------------------------|-------|---|-------------|------|
| | | | | Ø | Ø | Ø | | Ø | Ø | Ø | | |
| 1200313 MOST POPULAR UNIT | KF7T2000 | Adj to 2 m | 11 mm | ♀ | 21 mm | Ⓐ | AJ567 | ♂ | 21 mm | Ⓐ | KJ5024 | 0.74 |
| 1200324 | KF7T2500 | Adj to 2.5 m | 11 mm | ♀ | 21 mm | Ⓐ | AJ567 | ♂ | 21 mm | Ⓐ | KJ5024 | 0.80 |
| 1200311 | KF7T5000 | Adj to 5 m | 11 mm | ♀ | 21 mm | Ⓐ | AJ567 | ♂ | 21 mm | Ⓐ | KJ5024 | 0.92 |
| 1200312 | KF7T5000L | Adj to 5 m | 11 mm | ♀ | 21 mm | Ⓐ | AJ567 | ♂ | 21 mm | Ⓐ | KJ5024 | 0.92 |
| 1200316 | KF7T10000 | Adj to 10 m | 11 mm | ♀ | 21 mm | Ⓐ | AJ567 | ♂ | 21 mm | Ⓐ | KJ5024 | 1.43 |

NEW PROTECTA® POSITIONING LANYARD RANGE

The new PROTECTA® adjustment system has been improved to give the option to easily adjust the length of the lanyard during use. These new versions have a triple action carabiner AJ572 with a zinc plated steel snaphook (ref: AJ523) and are available in different lengths.

DESCRIPTION: Braided rope, diameter 10.5 mm.

MAX WEIGHT CAPACITY: 140 kg.



CE EN358 CE EN362

| New Ref | Old Ref | Adjustment | Rope Diameter | Triple Action Carabiner | | | Connector | Single Action Carabiner | | | Weight (kg) | |
|------------------------------|---------|------------|---------------|-------------------------|-------|---|-----------|-------------------------|-------|---|-------------|------|
| | | | | Ø | Ø | Ø | | Ø | Ø | Ø | | |
| 1200314 MOST POPULAR UNIT | AF777 | Adj to 2 m | 10.5 mm | ♀ | 21 mm | Ⓢ | AJ523 | ♂ | 24 mm | Ⓐ | AJ572 | 0.85 |
| 1200317 | AF777/1 | Adj to 3 m | 10.5 mm | ♀ | 21 mm | Ⓢ | AJ523 | ♂ | 24 mm | Ⓐ | AJ572 | 0.92 |
| 1200315 | AF777/2 | Adj to 4 m | 10.5 mm | ♀ | 21 mm | Ⓢ | AJ523 | ♂ | 24 mm | Ⓐ | AJ572 | 0.99 |



a 3M company

Now part of



A GLOBAL LEADER IN FALL PROTECTION

Capital Safety is a Global leader in fall protection equipment, systems and anchors.

Capital Safety est un leader mondial en matière d'équipement, de systèmes et d'ancrages de protections antichute.

Capital Safety ist ein weltweiter Führer auf dem Gebiet von Absturzsicherungs-ausrüstung, -systemen und Anschlagmöglichkeiten.

Capital Safety es un líder global en la protección anticaída para los dispositivos de protección individual, sistemas y puntos de anclaje.

Capital Safety is een wereldleider in valbeveiligingsapparatuur, -systemen en verankeringen.

Capital Safety è un leader globale nell'anticaduta per dispositivi di protezione individuale, sistemi e ancoraggi.

Capital Safety är globala inom utrustning, system och förankringar för fallskydd.

EUROPE, MIDDLE EAST & AFRICA

UK

5a Merse Road, North Moons Moat
Redditch, B98 9HL, UK
t: +44 (0) 1527 548 000
f: +44 (0) 1527 591 000

FRANCE

Le Broc Center, Bâtiment A
Z.1. 1re Avenue – BP15
06511 Carros Le Broc, Cedex, FRANCE
t: +33 (0) 4 97 10 00 10
f: +33 (0) 4 93 08 79 70

GERMANY

Hagener Straße 44
57489 Drolshagen, GERMANY
t: +49 (0) 2 76 18 33 82 29
f: +49 (0) 2 76 18 33 81 93

DUBAI

P.O. BOX 17769, Jebel Ali Free Zone
Jafza Lobby N° 15, Office N° 15315
(3rd Floor), DUBAI – UAE
t: +971 (0) 4 88 11 4 66
f: +971 (0) 4 88 11 4 67

All rights reserved. The material contained herein is copyrighted; no part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise without prior written permission from Capital Safety. Capital Safety Group (Northern Europe) Limited, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT. Registered in England and Wales No. 1918922.

CUSTOMER SERVICES

00 800 999 55500

information@capitalsafety.com

capitalsafety.com



@CapitalSafetyUK



facebook.com/CapitalSafety



youtube.com/CapitalSafetyEMEA